



Cannondale Trail SL

	XS	SM	MD	LG	XL
A Seat Tube Length (cm)	36.0	39.0	44.0	47.0	52.0
B Top Tube Horizontal (cm)	53.7	56.1	59.3	62.1	64.8
C Top Tube Actual (cm)	53.3	55.0	57.4	59.8	62.5
D Head Tube Angle	68.0°	68.0°	68.0°	68.0°	68.0°
E Seat Tube Angle	75.0°	75.0°	75.0°	75.0°	75.0°
E Seat Tube Angle Effective	74.0°	74.0°	74.0°	74.0°	74.0°
F Standover (cm)	71.6	73.9	77.4	79.6	83.2
G Head Tube Length (cm)	9.0	9.0	10.0	11.0	12.0
H Wheelbase (cm)	106.4	109.0	112.3	115.2	118.0
I Front Center (cm)	63.7	66.3	69.6	72.5	75.3
J Chain Stay Length (cm)	43.5	43.5	43.5	43.5	43.5
K Bottom Bracket Drop (cm)	6.5	6.5	6.5	6.5	6.5
L Bottom Bracket Height (cm)	31.1	31.1	31.1	31.1	31.1
M Fork Rake (cm)	5.1	5.1	5.1	5.1	5.1
N Trail (cm)	9.7	9.7	9.7	9.7	9.7
O Stack (cm)	58.4	59.8	60.8	61.7	62.6
P Reach (cm)	36.9	38.9	41.9	44.4	46.9